



PRODUCT DATA SHEET

NZ PAINT CO. LTD.

30 KLONDYKE DR, HORNBY SOUTH, CHRISTCHURCH

PRODUCT	ELASTOCOAT 300
Description	Acrylic Elastomeric coating with high elasticity. Utilises a high-performance polymer that is extremely resistant to yellowing or aging. Good UV absorber.
Uses	Waterproofing for all roofing substrates, walls, concrete renders and plasters. Is commonly used on Iron, Butynol and as an Asbestos encapsulation system usually as a topcoat to our penetrative sealer. Can be used as topcoat for leaky homes rectification. Is suitable for flat roofs with ponding.
Appearance	Satin
Colour Range	White, Grey or Tinted
Coverage	6-8m ² per litre
Surface Preparation	<ol style="list-style-type: none"> 1. Ensure surface is clean and free from grease and dirt. 2. Allow new concrete to cure for at least 28 days 3. Ensure Super6 Asbestos is free from moss by using moss and lichen killer. Do not waterblast asbestos. <p>CAUTION: Do not use any degreasing agents, waxes or detergents to clean surface before painting.</p>
Application	<ol style="list-style-type: none"> 1. Spray, roll or brush. Will operate through airless spray like Graco 395. Use 15/5 tip or similar. 2. Product should be thoroughly stirred for at least 5 minutes before use 3. Use Appropriate safety gear and planking when walking on Asbestos roofs.
Dry Time	Surface Dry: 30 Minutes Tack-Dry 2 hours Hard Dry 4 hours
Thinner	Water BUT NEVER thin. It will destroy the polymer strength of the paint.
Flash Point	Non-Flammable. No solvent.
Chemical Resistance	Excellent
Clean Up	Water
Container Sizes	4 Litre & 10 Litre
Coating Format	2 final coats. Within 72 hours. If sealant used leave for 24 hours before applying topcoat.
Risk Mitigation	<ol style="list-style-type: none"> 1. No protective clothing necessary but good ventilation required. 2. Is a suitable coating for collecting drinking water for human consumption. 3. Good ponding qualities
Our Suggestions	Do not apply when surface temperature below 3C or above 35C or rain imminent.

In the interest of personal safety NZ Paint Co Ltd recommend all paint products be stored securely away from children.

NZ Paint Co Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact NZ Paint Co free phone (0800) 80 PAINT (72468).

The information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond NZ Paint Co Ltd control. Some guarantees may apply by law.

www.nzpaint.co.nz