

PRODUCT DATA SHEET 3/2



ENVIROPAINTS LTD P.O.BOX 152 OTAKI 5542 0800503684

PRODUCT	
Description	Non Toxic Hardwearing product. Solvent based. GHS Classification 3.1c. One pot system.
Uses	Swimming Pools Also for paving and food processing walls. Will withstand high pressure water cleaning.
Appearance	Gloss
Colour Range	Swimming Pool Blue or Tinted 99/100 BS5252
Coverage	9m ² per litre
Surface Preparation	<ol style="list-style-type: none"> 1. Ensure surface is clean and dry and free from grease and dirt. 2. Dirt and Grime. Wash and scrop with water.Wash again.Leave to dry. 3. Oily Substances.Clean by rubbing with Dairycoat Thinners.. Wash and scrub with water and wash again. 4. If the surface is old with existing paint, we suggest you water blast. 5. Dry- to test if the surface is dry,tape a square of polythene to the surface,ensure it is secure all the way round (no air can enter).Leave overnight. If when removed the back of polythene is damp or substrate is different colour to surrounding area, DO NOT proceed as moisture is present. 6. Apply this product on a declining temperature between 10c-20c this allows the solvent to be sucked into the substrate. 7. If applied in the heat of the day small pinholing can occur as watervapour comes out of the substrate. <p>Caution: Do not use any degreasing agents, waxes or detergents to clean surface before painting</p>
Application	<ol style="list-style-type: none"> 1. Broom or brush 2. Do not use roller. 3. Recoat ½ hour. 4. Allow plenty of ventilation
Dry Time	30 minutes at normal temperature.
Thinner	Special Enviropaints thinners
Flash Point	Flammable
Chemical Resistance	
Clean Up	Enviropaints thinners
Container Sizes	1 Litre, 4 Litre, 10 Litre & 20 Litre
Coating Format	3 coats. Brush in a thinned first coat by 10%-15% to ensure a good key for your next two coats.
Risk Mitigation	<ol style="list-style-type: none"> 1. No protective clothing necessary but good ventilation required.
Our Suggestions	We supply the brooms.

In the interest of personal safety Enviropaints Ltd recommend all paint products be stored securely away from children.
 ENVIROPAINTS Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact Enviropaints free phone (0800) 80 PAINT (72468).
 THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond Enviropaints Ltd control. Some guarantees may apply by law.