

PRODUCT DATA SHEET 2/1



NZ PAINT CO. LTD P.O.BOX 152 OTAKI 5542 0800503684

PRODUCT	ACRO WONDER PRIMER/UNDERCOAT
Description	A high quality acrylic copolymer based primer/undercoat paint formulated especially as an intermediary coat between various substrates and Enviropaints Acro Enamel Gloss, Semi Gloss or Low Sheen. Coatings with this product will exceed end grain sealing qualities.
Uses	Rough sawn and dressed bare timber, all composite boarding (eg MDF, chip & bison board), sanded lamiwall, hardboard, aluminium mouldings, ceramic tiles, cement based plaster, masonry finishes, fibre cement boards. Sealer coat over old native timbers, sanded old polyurethanes and varnishes, pre primed metals, existing oil based coatings, gibraltor board, and pinex.
Adhesion	Excellent
Finish	Matt
Colour	Off White. - Can be tinted to pastel colours for better colour opacity build of dark coloured topcoats.
Dry Time	Touch dry 30 minutes, recoat 2 hours (depending on temperature and humidity)
Surface Preparation	
Application	Brush, roller, spray or airless spray. Ask your dealer for advice on special rollers and brushes available for this product.
Application Rate	10 -15 m2 per litre depending on surface texture.
Toxicity	Non Toxic, lead and heavy metal free
Thinner/Clean up	Water
Container Sizes	1 Litre, 4 Litre, 10 Litre, 20 Litre.
Surface Preparation	Ensure surfaces are dry, free from dirt, grease or other contamination and dust free. Pre-primed timber exposed for more than 2-3 weeks must be sanded and pre-primed again. Apply Enviropaints Acro Wonder Primer/Undercoat straight from the can. Should not require thinning.
General Precautions	<ul style="list-style-type: none"> • Do not apply Acro Wonder Primer/Undercoat when surface temperature below 10°C or above 30°C. • In Winter do not commence painting unless ambient temperature is above 13°C. Limit painting to between 10.30am and 3pm. We recommend not painting in very damp or humid conditions. • When painting opening sashes & doors, allow sufficient clearance after coating for ease of opening. • Stir well with a flat stirrer using an up and down scooping action before use. • Dampen pourous masonry surfaces before coating, especially in dry warm conditions. • Do not use over old lime wash or powdery surfaces. • Protect from freezing during storage

In the interest of personal safety NZ Paint Co. Ltd recommend all paint products be stored securely away from children. NZ Paint CO. Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact NZ Paint Co. free phone (0800) 80 PAINT (72468). THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond NZ Paint Co. Ltd control. Some guarantees may apply by law.