



PRODUCT DATA SHEET

NZ PAINT CO. LTD
 P.O.BOX 152
 OTAKI 5542
 0800 80 72468

PRODUCT	AQUA ROOF PRIMER
Description:	A high-quality acrylic copolymer based anti-corrosive paint formulated especially for use on galvanised iron, it can also be used as a primer for steelwork.
For Use On:	Galvanised iron, zinc, aluminium, steel, building styrene, concrete, fibre cement and masonry.
Finish:	Matt
Colour:	Grey/Green
Dry Time:	Touch dry 30 minutes depending on temperature and humidity. Recoat 2 hours
Application Rate:	15 m ² per litre
Toxicity:	Lead free - contains chromates
Chemical Resistance:	Moderate
Application:	Brush, roller or spray
Container Sizes:	1 Litre, 4 Litre, 10 Litre, 20 Litre.
Thinner/Clean Up:	Water
NOTE:	Does not initiate flash rust formation on clean steelwork.
Surface Preparation:	Thoroughly remove all dirt, grease or other contamination before painting. On new galvanised iron we recommend degreasing with hot detergent solution or sugar soap, using a soft broom, followed by thorough rinsing. If pre-painted waterblast to remove all loose and flaking paint, back to a sound surface. A scarifying nozzle tip is best.
General Precautions:	<p>(a) Do not apply Aqua Roof Primer at temperatures below 12°C or above 30°C. In hot weather work early morning or later afternoon to miss the intense heat of the day.</p> <p>(b) Overcoat within four weeks if used for exterior exposure conditions. Will require washing again if left for four weeks in coastal environments. If painting near the sea or in salty conditions hose surface with clean water and let dry between each coat. In heavy salt deposit areas, the use of a light hair broom, while hosing, is essential.</p> <p>(c) Stir well with a wide flat stirrer before use.</p> <p>(d) Dampen masonry surfaces before coating, especially in dry warm conditions.</p> <p>(e) we do not recommend painting Aqua Roof Primer in very damp conditions.</p> <p>(f) Protect from freezing during storage.</p>

In the interest of personal safety NZ Paint Co. Ltd recommend all paint products be stored securely away from children. NZ Paint Co. Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal or require Material Safety Handling information, please contact NZ Paint Co. free phone (0800) 80 PAINT (72468).

THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond NZ Paint Co. Ltd control. Some guarantees may apply by law.