



PRODUCT DATA SHEET

NZ PAINT CO. LTD

P.O.BOX 152

OTAKI 5542

0800 80 72468

| PRODUCT FENCECOAT | |
|---|---|
| Description: | Mixed oxides with added virgin vinyl copolymer, producing a low sheen paint exhibiting very good exterior coverage. |
| Uses: | Normally used to give a low sheen appearance on fences and exterior walls. Concrete, wood, and primed metal. (Not roof paint) |
| Finish: | Satin sheen 12% |
| Colour: | Redwood, Landscape Green, Concrete, White, Blue, Cedar, Dark Grey, Black, Karaka |
| Dry Time: | Touch dry 30 minutes Depending on temperature and humidity. Recoat in 2 hours |
| Number of coats: | On rough sawn timber, one or two coats. |
| Flash Point: | Not applicable. |
| Application Rate: | 9-10m ² per litre depending on surface texture. |
| Toxicity: | Non-toxic - lead and heavy metal free (dry film) |
| Adhesion: | Excellent |
| Durability: | Very good. |
| Application: | Brush, roller, or airless spray. |
| Solvent Resistant: | Fair |
| Primer Required: | No |
| Container Sizes: | 4 Litre, 10 Litre. Larger volumes on request. |
| Burnish Resistance: | Good, wipeable. |
| Thinner/Clean up: | Water |
| Surface Preparation: | Ensure surface to be painted is dry, free from dirt grease or other contamination, and dust free. Remove all loose flakey paint. Fill and sand nail holes and imperfections. If near the sea; salt will need to be removed with water before painting. |
| Precautions: | <ul style="list-style-type: none"> • Do not paint when surface temperature is below 10°C. • In winter, do not start painting unless ambient temperature is above 13°C, and limit painting between 10.30am and 3pm. We recommend not painting in very damp, humid, or frosty conditions. • Do not use on chalky or powdery surfaces. • Stir well with a wide flat stirrer before use. • Dampen porous masonry surfaces before coating, & especially in dry warm • For optimum drying conditions ensure a free flow of air especially in humid weather • Protect from freezing during storage. • Follow instructions on the pail. |

In the interest of personal safety NZ Paint Co. Ltd recommend all paint products be stored securely away from children. NZ Paint Co. Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal or require Material Safety Handling information, please contact NZ Paint Co. free phone (0800) 80 PAINT (72468).

THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond NZ Paint Co. Ltd control. Some guarantees may apply by law.