

PRODUCT DATA SHEET 14



NZ PAINT CO. LTD P.O.BOX 152 OTAKI 5542 0800503684

PRODUCT	Uniseal
Description	Non Toxic Hardwearing product. Solvent based acylic. GHS Classification 3.1c.Designed to give "natural look" protection.
Uses	Concrete,cement plaster.timber, tarnishable metals, brickwork and stone work. Commonly used to seal old concrete roof tiles and enhance water tightness after the roof substrate has been de-mossed and cleaned. Can be tinted to a range of colours and used on concrete driveways.
Appearance	Gloss or Matt
Durability	Excellent
Heat Resistance	Up to 80° C
Colour Range	Clear or or Tinted
Coverage	9m2 per litre
Surface Preparation	<ol style="list-style-type: none"> 1. Ensure surface is clean and dry and free from grease and dirt. 2. Dirt and Grime. Wash and scrub with water.Wash again. Leave to dry. 3. Oily Substances.Clean by rubbing with Thinners.. Wash and scrub with water and wash again. 4. If the surface is old with existing paint, we suggest you water blast. 5. Dry- to test if the surface is dry,tape a square of polythene to the surface,ensure it is secure all the way round (no air can enter).Leave overnight. If when removed the back of polythene is damp or substrate is different colour to surrounding area, DO NOT proceed if moisture is present. 6. Apply this product on a declining temperature between 10c-20c this allows the solvent to be sucked into the substrate. 7. If applied in the heat of the day small pinholing can occur as watervapour comes out of the substrate. <p>Caution: Do not use any degreasing agents, waxes or detergents to clean surface before painting</p>
Application	Brush or Spray.
Dry Time	20 minutes at normal temperature.
Thinner and Cleanup	Special Solvent
Flash Point	Flammable
Container Sizes	1 Litre, 4 Litre, 10 Litre & 20 Litre
Coating Format	3 coats. Brush in a thinned first coat by 10%-15% to ensure a good key for your next two coats.
Risk Mitigation	No protective clothing necessary, use respirator if spraying. Good ventilation is required.
Our Suggestions	We supply the brooms.

In the interest of personal safety NZ Paint Co. Ltd recommend all paint products be stored securely away from children.
 NZ PAINT CO. Ltd cares about the environment and our valued customers, if you have any questions on the product you are using from application to disposal, or require Material Safety Handling information please contact NZ Paint Co. free phone (0800) 80 PAINT (72468).
 THE information stated on this Data Sheet, to the best of our knowledge is true and accurate. Any recommendations or suggestions are given in good faith but without guarantee since conditions of use and application are beyond NZ Paint Co. Ltd control. Some guarantees may apply by law.